



# Product data sheet

Power tools for trade & industry

Charger

## GAL 18V6-80



Continuous charging for non-stop work – multi-bay charger with 6 battery interfaces

### The most important data

Charge current	8 A
Battery charging voltage	14.4 – 18 V
Weight	1,800 g

**Order number** 1 600 A01 U9P

[> More product information](#)

## Technical data

### Technical data

Battery charging voltage	14.4 – 18 V
Charge current	8 A
Charg. time at bat. cap. 2.0 Ah (80%/100%) approx.	16/24 min
Charg. time at bat. cap. 4.0 Ah (80%/100%) approx.	23/37 min
Charg. time at bat. cap. 5.0 Ah (80%/100%) approx.	28/47 min
Charg. time at bat. cap. 6.0 Ah (80%/100%) approx.	32/57 min
Charg. time ProCORE18V 4.0 Ah (80%/100%) approx.	32/50 min
Charg. time ProCORE18V 8.0 Ah (80%/100%) approx.	42/68 min
Charg. time ProCORE18V 12.0 Ah (80%/100%) approx.	65/96 min
Weight	1,800 g
Battery voltage	18 V



# Product data sheet

Power tools for trade & industry

## Advantages:

- Fast charging speed with 8A current – ProCORE18V 8.0Ah charges to 80% in 42 min
- Efficient charge – 2 charging cycles ensure continuous work
- Priority Start Button – easy prioritisation of a selected battery

