

People. Passion. Performance.

Item 1: 4116023045

Chicago Pneumatic Reciprocating: CPRD 6150 NS39 - 5.5hp on 150ltr tank



415V Three phase, Two Stage Heavy Duty Piston Compressor. 5.5 hp, 11bar

- Cast iron barrels
- · Aluminium Heads for faster cooling
- Auto On/Off pressure switch
- External Oil level gauge
- Industrial Paint Finish
- As1210 Certified air receiver
- 1 Year Warranty
- Made in ITALY

## **Specification:**

Air Receiver

•	Piston Displacement	23 cfm / 651 L/min
•	Free Air Delivered	18.4 cfm / 521 L/min
•	Max operating pressure	11 Bar / 160 psig
•	Min operating pressure	6 bar / 87 psig
•	Voltage	415/3/50 hz
•	Rated Motor Power	4kw
•	Pump Speed	1000 rpm
•	Breaker required	20 A type D motor starting *1
•	Type of Cooling	Air cooled
•	Noise level	95+ dBa at 1 metre
•	Air discharge Connection	1/2" BSP
•	Dimensions (L x W x H) mm	1560 x 580 x 1130
•	Weight	140 kg

150 L

<sup>\*1</sup> Only a Guideline. Qualified Electrician wiring the compressor has to do site specific calculation