



People. Passion. Performance.

Item 1: 4116022971

Chicago Pneumatic Reciprocating: CPRD 8200 NS39 -7.5 hp on 200ltr tank



415V Three phase, **Two Stage** Heavy Duty Piston Compressor. **7.5 hp**, 11bar

- Cast iron barrels
- Aluminium Heads for faster cooling
- Auto On/Off pressure switch
- External Oil level gauge
- Industrial Paint Finish
- As1210 Certified air receiver
- 1 Year Warranty
- **Made in ITALY**

Specification:

- | | |
|-----------------------------|-------------------------------|
| • Piston Displacement | 29.2 cfm / 826 L/min |
| • Free Air Delivered | 23.3 cfm / 661 L/min |
| • Max operating pressure | 11 Bar / 160 psig |
| • Min operating pressure | 6 bar / 87 psig |
| • Voltage | 415/3/50 hz |
| • Rated Motor Power | 5.5kw |
| • Pump Speed | 1250 rpm |
| • Breaker required | 20 A type D motor starting *1 |
| • Type of Cooling | Air cooled |
| • Noise level | 95+ dBa at 1 metre |
| • Air discharge Connection | 1/2" BSP |
| • Dimensions (L x W x H) mm | 1590 x 600 x 1150 |
| • Weight | 160 kg |
| • Air Receiver | 200 L |

***1 Only a Guideline. Qualified Electrician wiring the compressor has to do site specific calculation**

www.cpccompressors.com.au