
Scrubber dryers SC250


SC250 is scrubbing, sweeping and drying in every corner

The Nilfisk SC250 is a compact scrubber dryer for fast and effective cleaning of hard floors, which will take you into every corner and ensure efficient cleaning in both directions - also under furniture and shelves. You will get a light and productive machine with a low sound level suited for daytime cleaning as it is battery-driven. An attractive choice for shops, schools, restaurants, cafes, bakeries, fast food chains, hotels, cleaning companies, etc.

Productivity is high due to the sheer speed of the machine as it is sweeping, scrubbing and drying at the same time, moving both forward and backward. Debris, dirt and even the smallest dust particles are removed effectively by the 34 cm cylindrical brush. For more in-depth cleaning without sweeping feature a microfiber roller can be used as option.

When cleaning, you can lift the front squeegee from the user position for easy pick-up of larger debris without having to stop. With two different solution flows you can adjust so it fits the cleaning task. Two simple ways to save time and cost without compromising on the result.





- High cleaning performance: 34 cm cylindrical brush or microfiber roll
- · Productive: The 6 liter solution and recovery tank gives up to 40 minutes of working time without refill
- Powerful: Nilfisk 36V Lithium battery technology
- Easy to use: The ergonomic handle can be adjusted into different positions, used free floating or folded for storage
- · Intuitive and self-explaining: Informative display on the handle.
- Full control: OneTouch™ button is activating all essential functions and touch sensors in the handle provide an easy operation
- Non-stop cleaning: The two water/solution settings can be changed on-the-fly
- · Safe: Out of Water alarm protecting the machine
- · Convenient: Easy to carry and move due to its compact design and low weight
- Low TCO: Long lifetime with 'No tool' inspection, service and maintenance



| | Included accessories | Ref. no. | Min. required | SCRUBBER SC250 34C B EU/UK |
|---------------------|------------------------------------|------------|------------------|----------------------------------|
| Brush Cylindr | rical | | | |
| *** | BRUSH CYL 340MM MEDIUM NYLON WHITE | 9100002066 | 1 | • |
| Squeegee Blade | | | | |
| | SQUEEGEE 360MM PU 2 PCS SET | 9100002064 | 1 | • |
| Battery and Charger | | | | |
| 0 | BATTERY LI KIT INCL CHARGER EU UK | 9100002056 | 1 | • |
| Other | | | | |





Picture shown may not represent model quoted

Scrubber dryers SC250

SC250 is scrubbing, sweeping and drying in every corner

| Included accessories | Ref. no. | Min. required | SCRUBBER SC250 34C B EU/UK |
|----------------------------------|------------|------------------|----------------------------------|
| MINI CONTAINER PLAST. F DIRT SIP | 9100001964 | 1 | • |

SCRUBBER SC250 34C B EU/UK Model

Ref. no. 9087380020

PRODUCT FEATURES

| Compact design | • |
|---------------------------------------|---|
| Lithium battery | • |
| Delivered ready to use (full package) | • |
| One-Touch™ Button | • |
| Tank in tank solution | • |
| Scrubbing and sweeping | • |

| Voltage (V) 36 Insulation class III Rated power (W) 300 Power consumption (kW) 0.3 Vacuum motor power (W) 180 Sound pressure level at 1.5 m (dB(A) ISO 3744) 66 ±3 Productivity theoretical/actual (m²/h) 1360/680 Running time (min.) 40 Handle vibration level (m/s²) < 2.5 Water flow (l/m) 0.15/0.3 Solution/recovery tank (l) 6/6 Squeegee width (mm) 340 Brush pressure (kg) Max 12 Brush speed (RPM) 1000 Brush quantity and type 1 Cyl Length x width x height (mm) 630x425x400 Gross weight (gvw) (kg) 32 Net weight (kg) 25 Shipping weight (kg) 30 | Technical specifications | SCRUBBER SC250 34C B EU/UK |
|---|--|-------------------------------|
| Rated power (W) 300 Power consumption (kW) 0.3 Vacuum motor power (W) 180 Sound pressure level at 1.5 m (dB(A) ISO 3744) 66 ±3 Productivity theoretical/actual (m²/h) 1360/680 Running time (min.) 40 Handle vibration level (m/s²) < 2.5 | Voltage (V) | 36 |
| Power consumption (kW) 0.3 Vacuum motor power (W) 180 Sound pressure level at 1.5 m (dB(A) ISO 3744) 66 ±3 Productivity theoretical/actual (m²/h) 1360/680 Running time (min.) 40 Handle vibration level (m/s²) < 2.5 | Insulation class | III |
| Vacuum motor power (W) 180 Sound pressure level at 1.5 m (dB(A) ISO 3744) 66 ±3 Productivity theoretical/actual (m²/h) 1360/680 Running time (min.) 40 Handle vibration level (m/s²) < 2.5 | Rated power (W) | 300 |
| Sound pressure level at 1.5 m (dB(A) ISO 3744) 66 ±3 Productivity theoretical/actual (m²/h) 1360/680 Running time (min.) 40 Handle vibration level (m/s²) < 2.5 | Power consumption (kW) | 0.3 |
| Productivity theoretical/actual (m²/h) 1360/680 Running time (min.) 40 Handle vibration level (m/s²) < 2.5 | Vacuum motor power (W) | 180 |
| Running time (min.) 40 Handle vibration level (m/s²) < 2.5 | Sound pressure level at 1.5 m (dB(A) ISO 3744) | 66 ±3 |
| Handle vibration level (m/s²) < 2.5 | Productivity theoretical/actual (m²/h) | 1360/680 |
| Water flow (I/m) 0.15/0.3 Solution/recovery tank (I) 6/6 Squeegee width (mm) 340 Brush pressure (kg) Max 12 Brush speed (RPM) 1000 Brush quantity and type 1 Cyl Length x width x height (mm) 630x425x400 Gross weight (gvw) (kg) 32 Net weight (kg) 25 | Running time (min.) | 40 |
| Solution/recovery tank (I) Squeegee width (mm) Brush pressure (kg) Brush speed (RPM) Brush quantity and type Length x width x height (mm) Gross weight (gvw) (kg) Net weight (kg) 6/6 Max 12 1000 1 Cyl 630x425x400 32 Net weight (kg) | Handle vibration level (m/s²) | < 2.5 |
| Squeegee width (mm) Brush pressure (kg) Brush speed (RPM) Brush quantity and type Length x width x height (mm) Gross weight (gvw) (kg) Net weight (kg) 340 Max 12 1000 1000 630x425x400 32 Net weight (kg) | Water flow (I/m) | 0.15/0.3 |
| Brush pressure (kg) Brush speed (RPM) Brush quantity and type Length x width x height (mm) Gross weight (gvw) (kg) Net weight (kg) Max 12 1000 630x425x400 32 Net weight (kg) | Solution/recovery tank (I) | 6/6 |
| Brush speed (RPM) Brush quantity and type Length x width x height (mm) Gross weight (gvw) (kg) Net weight (kg) 1000 1 Cyl 630x425x400 32 Net weight (kg) | Squeegee width (mm) | 340 |
| Brush quantity and type Length x width x height (mm) Gross weight (gvw) (kg) Net weight (kg) 1 Cyl 630x425x400 32 Net weight (kg) | Brush pressure (kg) | Max 12 |
| Length x width x height (mm) Gross weight (gvw) (kg) Net weight (kg) 630x425x400 32 25 | Brush speed (RPM) | 1000 |
| Gross weight (gvw) (kg) Net weight (kg) 32 | Brush quantity and type | 1 Cyl |
| Net weight (kg) 25 | Length x width x height (mm) | 630x425x400 |
| | Gross weight (gvw) (kg) | 32 |
| Shipping weight (kg) 30 | Net weight (kg) | 25 |
| | Shipping weight (kg) | 30 |



Scrubber dryers SC250

SC250 is scrubbing, sweeping and drying in every corner

 \bullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

| | Accessories | Ref. no. | Min. required | SCRUBBER SC250 34C B EU/UK |
|---|--------------------------------------|------------|------------------|----------------------------------|
| Brush Cylindri | cal | | | |
| | BRUSH CYL 340MM GRIT 320 GREY | 9100002067 | 1 | 0 |
| * | BRUSH CYL 340MM MEDIUM NYLON WHITE | 9100002066 | 1 | • |
| | BRUSH CYL 340MM MICROFIBRE | 9100002068 | 1 | O |
| | BRUSH CYL 340MM SOFT NYLON BLACK | 9100002069 | 1 | O |
| Other | | | | |
| | MINI CONTAINER PLAST. F DIRT SIP | 9100001964 | 1 | • |
| Battery and C | harger | ' | | |
| | BATTERY FAST CHARGER LI 500W - EU | 41600864 | 1 | O |
| | BATTERY FAST CHARGER LI 500W - UK/CH | 41600865 | 1 | 0 |
| OF STATE OF | BATTERY LI KIT INCL CHARGER EU UK | 9100002056 | 1 | • |
| Squeegee Blade | | | | |
| | SQUEEGEE 360MM PU 2 PCS SET | 9100002064 | 1 | • |

